




* General Description


BYD IGBT Power Module BG600F08B14L5-L provides low switching loss as well as compact & high power density design, which introduce the advanced trench & field stop IGBT chip and ultra fast & soft recovery anti-parallel FRD to improved connection, it is able to take on a perfect performance in various applications up to 10KHz.

比亚迪IGBT功率模块 BG600F08B14L5-L 提供低损和紧凑型高功率密度设计,内含高性能的沟槽栅场终止技术IGBT和超快速软恢复二极管芯片,在不超过10KHZ频率的应用中表现出优良的性能。



* Key Features

- Full bridge module
全桥模块
- Compact & High power density design
紧凑型高功率密度设计
- 750V trench&field stop technology
750V 沟槽栅场终止技术
- Ultra low conduction and switching loss
低导通和开关损耗
- Including ultra fast & soft recovery anti-parallel
FRD
反并联超快速软恢复二极管
- RoHS compliant
符合RoHS标准



* Applications

- AC motor control
交流马达控制
- Inverters
逆变器
- Servo
伺服电机



* IGBT

□ Maximum Rated Values/最大额定值

Symbol	Items	Conditions	Value	Unit
V_{CES}	Collector-emitter voltage 集电极-发射极电压	$T_{vj}=25^{\circ}\text{C}$	750	V
I_{C_nom}	Continuous DC Collector current 连续集电极直流电流	$T_F=25^{\circ}\text{C}, T_{vj}=175^{\circ}\text{C}$	600	A
		$T_F=65^{\circ}\text{C}, T_{vj}=150^{\circ}\text{C}$	450	A
V_{GES}	Gate-emitter voltage 栅极-发射极峰值电压	$T_{vj}=25^{\circ}\text{C}$	± 20	V
I_{CRM}	Repetitive peak collector current 集电极重复峰值电流	Pluse, $t_p=1\text{ms}, T_{vj}=25^{\circ}\text{C}$	1200	A
I_{SC}	SC data 短路数据	$V_{GE} \leq 15\text{V}, V_{CC}=400\text{V}$ $V_{CEmax}=V_{CES}-LsCE \cdot di/dt$ $t_p \leq 5\mu\text{s}, T_{vj}=25^{\circ}\text{C}$ $t_p \leq 3\mu\text{s}, T_{vj}=150^{\circ}\text{C}$	4550	A
			3500	A
P_{tot}	Total power dissipation 总耗散功率	$T_F=75^{\circ}\text{C}, T_{vj}=175^{\circ}\text{C}$	775	W

□ Characteristics Values/特征值

Symbol	Items	Conditions	Value			Unit
			Min.	Typ.	Max.	
VCE sat	Collector-Emitter Saturation Voltage 集电极-发射极饱和电压	$IC=600\text{A}, VGE=15\text{V}, T_{vj}=25^{\circ}\text{C}$	-	1.55	-	V
		$IC=600\text{A}, VGE=15\text{V}, T_{vj}=125^{\circ}\text{C}$	-	1.70	-	V
		$IC=600\text{A}, VGE=15\text{V}, T_{vj}=150^{\circ}\text{C}$	-	1.75	-	V
VGEth	Gate threshold voltage 栅极阈值电压	$VCE=VGE, IC=12\text{mA}, T_{vj}=25^{\circ}\text{C}$	5.0	6.0	7.0	V
QG	Gate charge 栅极电荷	$VGE=-9\text{V} \dots +15\text{V}, VCC=0\text{V}$	-	1.86	-	uC
Rgint	Internal gate resistance 内部栅极电阻	$T_{vj}=25^{\circ}\text{C}$ $f=300\text{KHz}, Vce=50\text{V}, Vge=0\text{V}$	-	1.6	-	Ω
Cies	Input capacitance 输入电容	$T_{vj}=25^{\circ}\text{C}, VGE=0\text{V}$ $f=300\text{KHz}, Vce=50\text{V}$ $Vge=0\text{V}$	-	50	-	nF
Coes	Output capacitance 输入电容		-	1.5	-	nF
Cres	Reverse capacitance 反向传输电容		-	0.1	-	nF
ICES	Collector-emitter cut-off current 集电极-发射极截止电流	$VCE=750\text{V}, VGE=0\text{V}, T_{vj}=25^{\circ}\text{C}$	-	-	1.0	mA
IGES	Gate-emitter leakage current 栅极-发射极漏电流	$VCE=0\text{V}, VGE=20\text{V}, T_{vj}=25^{\circ}\text{C}$	-	-	400	nA



tdon	Turn-on delay time 开通延迟时间	IC = 450 A VCE = 400 V VGE=-8V...+15 V RGon = 2.5Ω RGoff=5Ω Ls=30nH	Tvj=25°C	-	160	-	ns	
			Tvj=125°C	-	155	-	ns	
			Tvj=150°C	-	150	-	ns	
tr	Rise time 上升时间		Tvj=25°C	-	70	-	ns	
			Tvj=125°C	-	75	-	ns	
			Tvj=150°C	-	75	-	ns	
td off	Turn-off delay time 关断延迟时间		Tvj=25°C	-	350	-	ns	
			Tvj=125°C	-	400	-	ns	
			Tvj=150°C	-	410	-	ns	
tf	Fall time 下降时间		Tvj=25°C	-	150	-	ns	
			Tvj=125°C	-	200	-	ns	
			Tvj=150°C	-	200	-	ns	
Eon	Turn-on energy loss 开通损耗能量		Tvj=25°C	-	10	-	mJ	
			Tvj=125°C	-	13	-	mJ	
			Tvj=150°C	-	14	-	mJ	
Eoff	Turn-off energy loss 关断损耗能量		Tvj=25°C	-	18	-	mJ	
			Tvj=125°C	-	23	-	mJ	
			Tvj=150°C	-	24	-	mJ	

□ FRD/二极管

□ Maximum Rated Values/最大额定值

Symbol	Items	Conditions	Value	Unit
VRRM	Repetitive peak reverse voltage 反向重复峰值电压	Tvj=25°C	750	V
IF	Forward current of diode 连续正向直流电流	-	600	A
IFRM	Repetitive peak forward current 正向重复峰值电流	Pluse, tp=1ms, Tvj=25°C	1200	A

□ Characteristics Values/特征值

Symbol	Items	Conditions	Value			Unit	
			Min.	Typ.	Max.		
VF	Forward voltage 正向电压	IF=600A VGE=0V	Tvj=25°C	-	1.60	-	V
			Tvj=125°C	-	1.55	-	V
			Tvj=150°C	-	1.50	-	V
IRM	Peak reverse recovery current 反向恢复峰值电流	IF=450 A VR = 400 V VGE=-8V di/dt=5500A/us	Tvj=25°C	-	180	-	A
			Tvj=125°C	-	250	-	A
			Tvj=150°C	-	270	-	A
Qr	Recovered charge 恢复电荷	Tvj=25°C Tvj=125°C Tvj=150°C	Tvj=25°C	-	10	-	uC
			Tvj=125°C	-	30	-	uC
			Tvj=150°C	-	33	-	uC




E _{rec}	Reverse recovery energy 反向恢复损耗		T _{vj} =25°C	-	4	-	mJ
			T _{vj} =125°C	-	11	-	mJ
			T _{vj} =150°C	-	12	-	mJ

• **Module/模块**

Symbol	Items	Conditions	Value			Unit
			Min.	Typ.	Max.	
T _{vjmax}	Maximum junction temperature 最大结温	for 10s within a period of 30s, occurrence maximum 3000times over lifetime	150	-	175	°C
T _{vjop}	Temperature under switching conditions 工作结温	Operating junction temperature continuous	-40	-	150	°C
T _{stg}	Storage temperature 储存温度	Storage Temperature Range	-40	-	125	°C
R _{thjF IGBT}	IGBT, thermal resistance, junction to coolant 结-冷却液热阻	per IGBT 单个IGBT	-	0.129	0.140	K/W
R _{thjF Diode}	Diode, thermal resistance, junction to coolant 结-冷却液热阻	per diode 单个二极管	-	0.175	0.200	K/W
L _{sCE}	-	-	-	8.5	-	nH
R _{CCE' + EE'}	Module lead resistance, terminals - chip 模块引线电阻, 端子-芯片	T _{vj} =25°C, per switch	-	0.8	-	mΩ
V _{isol}	Isolation test voltage 绝缘测试电压	RMS, f = 50Hz, t = 30s	3800	-	-	V
m	Weight 重量	-	-	710	-	g
dCreep	Creepage distance 爬电距离	Terminal to terminal 端子到端子	-	9.0	-	mm
		Terminal to base 端子到底板	-	9.0	-	
dClear	Clearance 电气间隙	Terminal to terminal 端子到端子	-	4.5	-	mm
		Terminal to base 端子到底板	-	4.5	-	
M ₁	Mounting torque for module mounting 模块的安装扭距	Screw M4-baseplate to heatsink Screw EJOT Delta PT WN5451 30x10-PCB to frame	1.8 0.45	2.0 0.5	2.2 0.55	N.m
M ₂	Terminal connection torque 端子的连接扭距	Screw M5-terminal to terminal	3.0	-	6.0	N.m
-	Internal isolation 内部绝缘	Ceramics 陶瓷	Al ₂ O ₃			-
-	Material of module baseplate 模块基板材料	-	Cu			-
L x W x H	Dimensions 尺寸	-	154.5×142.5×32			mm

• **NTC-Thermistor/负温度系数热敏电阻**

Symbol	Items	Conditions	Value			Unit
			Min.	Typ.	Max.	
R ₂₅	Rated resistance 额定电阻值	T _c =25°C	-	5.0	-	kΩ
△R/R	Deviation of R100 R100 偏差	T _c =100°C, R ₁₀₀ =493Ω	-5	-	5	%
P ₂₅	Power dissipation 耗散功率	T _c =25°C	-	-	20	mW
B _{25/50}	B-value/B-值	R ₂ =R ₂₅ exp[B _{25/50} (1/T ₂ -1/(298.15K))]	-	3375	-	K
B _{25/80}	B-value/ B-值	R ₂ =R ₂₅ exp[B _{25/80} (1/T ₂ -1/(298.15K))]	-	3411	-	K
B _{25/100}	B-value/ B-值	R ₂ =R ₂₅ exp[B _{25/100} (1/T ₂ -1/(298.15K))]	-	3433	-	K

 Characteristics Diagrams/特性曲线





Fig.3: Transfer Characteristics
图3：传输特性




Fig.4: Switching Loss vs. Collector Current
图4：开关损耗与集电极电流关系




Fig.5: Switching Loss vs. Gate Resistor
图5：开关损耗与门极电阻关系






Fig.6: Switching Times vs. Gate Resistor
图6：开关时间与门极电阻关系






Fig.11: Reverse Bias Safe Operating Area
图11：反偏安全工作区




Fig.12:Typ. NTC-Temperature Characteristics
图12：典型的NTC电阻-温度特性




Fig.13: Typ. transient thermal impedance(IGBT)
 Z_{thJF} IGBT(K/W)
图13：典型的瞬态热阻抗(IGBT) Z_{thJF} IGBT(K/W)







Fig.14: Typ. transient thermal impedance(FRD)
 Z_{thJF} FRD(K/W)
图14：典型的瞬态热阻抗(FRD) Z_{thJF} FRD(K/W)



□ Circuit Diagram/接线图



● Package outlines/封装尺寸





● Attention

Correct and Safety Use of Power Module

Unsuitable operation (such as electrical, mechanical stress and so on) may lead to damage of power modules.

Please pay attention to the following descriptions and use BYD's IGBT modules according to the guidance.

During Transit:

- Tossing or dropping of a carton may damage devices inside.
- If a device gets wet with water, malfunctioning and failure may result. Special care should be taken during rain or snow to prevent the devices from getting wet.

Storage:

- The temperature and humidity of the storage place should be 5~35°C and 45~75% respectively. The performance and reliability of devices may be jeopardized if devices are stored in an environment far above or below the range indicated above.

Prolonged Storage:

- When storing devices more than one year, dehumidifying measures should be provided for the storage place. When using devices after a long period of storage, make sure to check the exterior of the devices is free from scratches, dirt, rust, and so on.

Operating Environment:

- Devices should not be exposed to water, organic solvents, corrosive gases, explosive gases, fine particles, or corrosive agents, since any of those can lead to a serious accident.

Anti-electrostatic Measures:

- Following precautions should be taken for gated devices to prevent static buildup which could damage the devices.

(1) Precautions against the device rupture caused by static electricity

Static electricity of human bodies and cartons and/or excessive voltage applied across the gate to emitter may damage and rupture devices. Sense-emitter and temperature-sensor are also vulnerable to excessive voltage. The basis of anti-electrostatic is suppression of build-up and quick dissipation of the charged electricity.

- Containers that are susceptible to static electricity should not be used for transit or for storage.
- Signal terminals to emitter should be always shorted with a carbon cloth or the like until right before a module is used. Never touch the signal terminals with bare hands.
- Always ground the equipment and your body during installation (after removing a carbon cloth or the like. It is advisable to cover the workstation and its surrounding floor with conductive mats and ground them.
- Use soldering irons with grounded tips.

BYD Semiconductor Co., Ltd. exerts the greatest possible effort to ensure high quality and reliability. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing BYD products, to comply with the standards of safety in making a safe design for the entire system, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue. In developing your designs, please ensure that BYD products are used within specified operating ranges as set forth in the most recent BYD products specifications.

□ 警示

功率模块安全正确的使用方法:

不当的操作（如电应力、机械应力等）可能导致模块损毁。请注意以下介绍，并根据指导来使用使用比亚迪IGBT模块。

**运输过程中：**

- 包装箱颠簸或坠落可能导致内部器件损毁。
- 器件遇水受潮将导致故障失效。在雨雪天气尤其要注意保护器件防止淋湿。

贮存：

• 贮存地点温度与湿度应分别控制在5~35°C和45~75%。如果贮存环境远高于或低于指示的变化范围，将危害器件的性能与可靠性。

长期贮存：

- 当存储器件时间超过一年，贮存地点应当采取去湿措施。器件经过长期存放使用时，检查器件确保外观没有刮伤，灰尘，锈迹等。

应用环境：

- 器件不应当暴露在水，有机溶剂，腐蚀性气体、易燃易爆性气体，微尘，腐蚀性药剂中，上述任何一种情况都会导致严重事故。

防静电措施：

- 带栅极器件应采取以下预警来防止可以损毁器件的静电生成。

(1) 预防措施可以防止静电击穿器件。

- * 门极与发射极间产生的人体静电、包装箱静电和过电压将损毁或击穿器件。采样发射极和温度传感器同样容易受到过压损毁。防静电底板可以抑制电荷生成并快速耗散。
- * 不要用易受静电影响的容器运输或贮存器件。
- * 发射极信号端子应一直用碳纤维布或类似物短接直到模块使用前。任何情况下不要徒手碰触信号端子。
- * 安装过程中始终保持设备和你的身体接地(移除碳纤维布或类似物后)。用导电垫覆盖工作地点及周围地板并使其接地。
- * 使用接地的烙铁头。 比亚迪半导体有限公司致力于产品的高性能和高可靠性.然而,半导体器件一般会因为其固有的对电荷敏感性和易受物理应力损坏的特点，而发生故障和失效.当用户购买BYD的产品时,用户有责任按照安全标准来为整个系统做出安全的设计来防止任何事 故，火灾或继而引起的危害公共安全，包括设计的冗余,防火措施,故障预防。请改善您的设计,确保BYD的产品在额定范围内使用 并参考最新的BYD产品规格书。

□ Revision History/版本更新履历

版本	日期	更新内容
A.0	2022.4.15	初版
A.1	2022.12.28	增加版本更新履历表，更新公司LOGO，更新模块外观图（外框变更），外框颜色由黑色调整为咖啡色